



Current A	Wattage W	Base	axial light intensity kcd	Average life hrs.	Fig.
6,6	30	cable flat female connector ³⁾	min. 16	1000	2
6,6	35	GZ4	min. 4,5	1500	3
6,6	40	cable round female connector ¹⁾	min. 10,5	1500	1
6,6	40	cable flat male connector ²⁾	min. 10,5	1500	1
6,6	40	cable flat female connector ³⁾	min. 10,5	1500	1
6,6	45	cable flat female connector ³⁾	min. 19,0	2500	2
6,6	45	cable round female connector ¹⁾	min. 19,0	2500	2
6,6	48	cable flat female connector ³⁾	min. 20,0	2500	2
6,6	48	cable flat male connector ²⁾	min. 20,0	2500	2
6,6	48	cable round female connector ¹⁾	min. 20,0	2500	2
6,6	48	cable round female connector ¹⁾	min. 23,0	1000	2
6,6	48	cable flat female ⁶⁾	min. 23,0	1000	2
6,6	48	cable flat male / female connector ⁵⁾	min. 25,0	500	2
6,6	62	cable flat female connector ^{1) 4)}	-	1500	2
6,6	62	GX5,3	-	1500	-
6,6	105	cable round female connector ¹⁾	min. 30,0	1000	2
6,6	105	cable flat female connector ³⁾	min. 30,0	1000	2
6,6	105	cable flat male connector ²⁾	min. 30,0	1000	2

Halogen airfield lamps – Dichroic reflector